



Plug socket □ MSSD-F-S-M16

URL: <https://www.sxplc.com/plug-socket-mssd-f-s-m16>

Product data sheet

- **Frequency of connection** 50
- **Cable outlet** Angled
- **Note on cable outlet** 180° rotatable
- **Product weight** 35 g
- **Electrical connection 1, design** Angular
- **Electrical connection 1, connection type** Socket
- **Electrical connection 1, connector system** Plug pattern type B to industry standard, 11 mm
- **Electrical connection 1, number of connections/cores** 3
- **Electrical connection 1, type of mounting** On solenoid valve via M3 central screw
- **Electrical connection 1, connection pattern** 00995619
- **Electrical connection 2, connector system** Screw terminal
- **Operational voltage range DC** 0 V ... 250 V
- **Operational voltage range AC** 0 V ... 250 V

- **Current rating at 40° C** 6 A
- **Immunity to surge** 2 kV
- **Protective conductor connection** Available
- **Cable fitting** M16x1.5
- **Cable diameter** 6 mm ... 8 mm
- **Nominal cross section conductor** $\leq 0.75 \text{ mm}^2$
- **Degree of protection** IP65
- **Note on degree of protection** In assembled state
- **Ambient temperature** -20 °C ... 115 °C
- **LABS (PWIS) conformity** VDMA24364-B2-L
- **Note on materials** RoHS-compliant
- **Pollution degree** 3
- **Corrosion resistance class** CRC1 - Low corrosion stress
- **Material housing** PA-reinforced
- **Housing colour** Black
- **Material seals** HNBR

