



Wall-mounted cooling unit, SK

3304.600

URL:<https://www.sxplc.com/wall-mounted-cooling-unit->

sk-3304-600

Product data sheet

	SK 3304.600
Design	wall-mounted
Product description	Energy-efficient Blue e wall-mounted cooling units in the output categories 300 W to 4000 W and with integral electrical condensate evaporator (from 1000 W).
Benefits	May be linked to the IoT interface via Blue e IoT adaptor for cooling units from 500 W cooling output with e-Comfort controller
Material	Stainless steel 1.4301 (AISI 304)
Colour	RAL 9007
Supply includes	Condenser with hydrophobic RiNano coating Fully wired ready for connection (plug-in terminal strip) Drilling template Assembly parts Integral electric condensate evaporation

Total cooling output to DIN EN 14511

Cooling output L35 L35/50 Hz: 1.1 kW
Cooling output L35 L35/60 Hz: 1.25 kW
Cooling output L35 L50/50 Hz: 0.91 kW
Cooling output L35 L50/60 Hz: 0.9 kW

Rated operating voltage

230 V, 1~, 50 Hz/60 Hz

Rated current max.

At 50 Hz: 3.9 A
At 60 Hz: 4.3 A

Start-up current max.

At 50 Hz: 12 A
At 60 Hz: 14 A

Air throughput (unimpeded air flow)

External circuit: 805 m³/h
Internal circuit: 600 m³/h

Energy efficiency ratio (EER) 50/60 Hz L35 L35

Refrigeration factor L35 L35 (EER) 50 Hz: 1.83
Refrigeration factor L35 L35 (EER) 60 Hz: 1.84

Design

wall-mounted

Dimensions

Width: 400 mm
Height: 950 mm
Depth: 260 mm

Protection category to IEC 60 529

External circuit IP 34
Internal circuit IP 54

Protection category NEMA

UL Type 12

Refrigerant/cooling medium

Refrigerant: R134a
Quantity: 0.325 kg
Global Warming Potential (GWP): 1,430
CO₂ equivalent (CO₂e): 0.46 t

Temperature control

e-Comfort controller (factory setting +35 °C)

Operating temperature range

10 °C...55 °C

Storage temperature range

-40 °C...70 °C

Setting range

20 °C...55 °C

