


EX-PROOF SOLENOID VALVE

DHA-0631/2/M 24DC

URL: <https://www.sxplc.com/ex-proof-solenoid-valve-dha-0631-2-m-24dc>

Product data sheet

DHA	/	*	-	0	63	/	1/2	/	M	/	*	24DC	/	**	/	*	
<p>Ex-proof solenoid directional valve, direct operated</p> <p>Certification type: Multicertification ATEX, IECEx, EAC: - = omit for Group II 2G / II 2D (1) M = Group I M2 (mining) North American Certification: UL = cULus</p> <p>Valve size (ISO 4401) 0 = 06</p>																	<p>Seals material, see section 6 :</p> <p>- = NBR PE = FKM BT = HNBR (1)</p> <p>Series number</p> <p>Voltage code, see section 5</p> <p>Options (3): A = solenoid at side of port B (for single solenoid valves) O = horizontal cable entrance (2) WP = ⚠ manual override protected by metallic cap Hand lever options (4): MV = vertical hand lever AMV = vertical hand lever installed at side of port B</p> <p>Solenoid threaded connection for cable gland fitting: GK = GK-1/2" - not for cULus M = M20x1,5 - not for cULus NPT = 1/2" NPT</p>
<p>Configuration, see section 2 :</p>  <p>Spool</p>																	