



Air solenoid valve VUVG-B10-T32C- AZT-F-1P3

URL:<https://www.sxplc.com/air-solenoid-valve-vuvg-b10-t32c-azt-f-1p3>

Product data sheet

- | |
|--|
| • Valve function 2x3/2, closed, monostable |
| • Actuation type Electrical |
| • Valve size 10 mm |
| • Standard nominal flow rate 150 l/min ... 170 l/min |
| • Pneumatic working port Flange |
| • Operating voltage 24V DC |
| • Operating pressure 0.15 MPa ... 1 MPa |
| • Operating pressure 1.5 bar ... 10 bar |
| • Structural design Piston gate valve |
| • Reset method Pneumatic spring |
| • Certification RCM compliance mark c UL us - Recognized (OL) |
| • Degree of protection IP40 IP65 With plug socket |
| • Nominal width 2.7 mm |
| • Exhaust air function With flow control option |

- **Sealing principle**Soft
- **Mounting position**Any
- **Manual override**Detenting Non-detenting Covered
- **Type of control**Pilot-controlled
- **Pilot air supply port**External
- **Symbol**00992905
- **Lap**Overlap
- **Pilot pressure MPa**0.15 MPa ... 0.8 MPa
- **Pilot pressure**1.5 bar ... 8 bar
- **Suitability for vacuum**no
- **Switching time off**15 ms
- **On switching time**6 ms

