



## **Air solenoid valve VUVG-B10-T32C- AZT-F-1P3**

URL:<https://www.sxplc.com/air-solenoid-valve-vuvg-b10-t32c-azt-f-1p3>

### **Product data sheet**

- **Valve function** 2x3/2, closed, monostable
- **Actuation type** Electrical
- **Valve size** 10 mm
- **Standard nominal flow rate** 150 l/min ... 170 l/min
- **Pneumatic working port** Flange
- **Operating voltage** 24V DC
- **Operating pressure** 0.15 MPa ... 1 MPa
- **Operating pressure** 1.5 bar ... 10 bar
- **Structural design** Piston gate valve
- **Reset method** Pneumatic spring
- **Certification** RCM compliance mark c UL us - Recognized (OL)
- **Degree of protection** IP40 IP65 With plug socket
- **Nominal width** 2.7 mm
- **Exhaust air function** With flow control option

- **Sealing principle**Soft
- **Mounting position**Any
- **Manual override**Detenting Non-detenting Covered
- **Type of control**Pilot-controlled
- **Pilot air supply port**External
- **Symbol**00992905
- **Lap**Overlap
- **Pilot pressure MPa**0.15 MPa ... 0.8 MPa
- **Pilot pressure**1.5 bar ... 8 bar
- **Suitability for vacuum**no
- **Switching time off**15 ms
- **On switching time**6 ms

