



Air solenoid valve VUVG- B10-M52-RZT-F-1P3

URL:<https://www.sxplc.com/air-solenoid-valve-vuvg-b10-m52-rzt-f-1p3>

Product data sheet

- **Valve function**5/2, monostable
- **Actuation type**Electrical
- **Valve size**10 mm
- **Standard nominal flow rate**210 l/min ... 330 l/min
- **Pneumatic working port**Flange
- **Operating voltage**24V DC
- **Operating pressure**-0.09 MPa ... 1 MPa
- **Operating pressure**-0.9 bar ... 10 bar
- **Structural design**Piston gate valve
- **Reset method**Mechanical spring Pneumatic spring
- **Certification**RCM compliance mark c UL us - Recognized (OL)
- **Degree of protection**IP40 IP65 With plug socket
- **Nominal width**4 mm
- **Exhaust air function**With flow control option

- **Sealing principle**Soft
- **Mounting position**Any
- **Manual override**Detenting Non-detenting Covered
- **Type of control**Pilot-controlled
- **Pilot air supply port**External
- **Symbol**00992849
- **Lap**Overlap
- **Pilot pressure MPa**0.25 MPa ... 0.8 MPa
- **Pilot pressure**2.5 bar ... 8 bar
- **Suitability for vacuum**yes
- **Switching time off**17 ms
- **On switching time**7 ms

