



Fan unit,SK 3244.100

URL:<https://www.sxplc.com/fan-unit-sk-3244-100>

Product data sheet

SK 3244.100	
version	wall-mounted
Product description	Filter fans with diagonal fan technology are more pressure-resistant and produce more constant air performance. The diagonal outflow direction ensures a more uniform heat dissipation from the enclosure.
Color	RAL 7035
Supply includes	Complete unit ready to install, including fleece filter mat
Fan	Diagonal, 1~ capacitor motor
Unimpeded air flow (with fleece filter)	At 50 Hz: 700 m ³ /h At 60 Hz: 770 m ³ /h (At 50 Hz: 412 cfm At 60 Hz: 453.2 cfm)
Unimpeded air flow (with folded filter)	At 50 Hz: 855 m ³ /h At 60 Hz: 905 m ³ /h

(At 50 Hz: 503.23 cfm
At 60 Hz: 532.66 cfm)

Air throughput with outlet filter incl. fleece filter mat (quantity x order number)

1 x 3243200: 485/520 m³/h

2 x 3243200: 570/630 m³/h

Rated operating voltage

230 V, 1~, 50 Hz/60 Hz

Rated power P_{el}

At 50 Hz: 95 W

At 60 Hz: 135 W

Rated current max.

At 50 Hz: 0.43 A

At 60 Hz: 0.6 A

Dimensions

Width: 323 mm

Height: 323 mm

(Width: 12.7 "

Height: 12.7 ")

